

**IN THE CLAIMS:**

**Please amend the original claims as follows.**

1. (Currently Amended) A holster holder for securing a holster to a wearer in a desired attitude, the holster holder comprising:
  - a plate;
  - a first arcuate slot defined through the plate, wherein the first arcuate slot is capable of allowing and comprising a first fastening means to extend extending therethrough;
  - a second arcuate slot defined through the plate, wherein the second arcuate slot is capable of allowing opposite to the first arcuate slot, and comprising a second fastening means to extend extending therethrough;
  - a third recurvate slot defined through the plate below the first and second slots, the third slot having a recurvate mustache shape, wherein the third slot is capable of allowing and comprising a third fastening means to extend extending therethrough;
  - wherein the three fastening means are capable of engaging three points of attachment defined on a holster;
  - and wherein a ~~the~~ relative angle of the holster to the plate is adjustable by coordinated adjustment of the three fastening means within each of the three slots.
2. (Currently Amended) The holster holder set forth in claim 1 wherein the holster is adjustable to predefined angles based upon the positioning of the three fastening means in selected indents formed in a ~~the~~ plate wall for engaging the fastening means.
3. (Original) The holster holder set forth in claim 1 wherein the three fastening means comprise screws.
4. (Currently Amended) The holster holder set forth in claim 2 wherein the fastening means comprise screws and wherein the selected indents formed in the plate wall engage a head portion ~~the heads~~ of the screws.

5. (Original) The holster holder set forth in claim 1 further comprising at least two further slots defined through the plate for receiving and securing the plate to a wearer's belt.

6. (Original) The holster holder set forth in claim 5 wherein each of the at least two belt receiving slots further comprises adjustment means for adjusting the height and the angle at which the belt passes through the slot.

7. (Original) The holster holder set forth in claim 2 wherein the plate comprises at least three belt receiving slots defined therethrough and wherein two of the belt receiving slots are formed in a vertical manner such that one is above the other, thereby providing alternative paths for the belt through the plate, thereby providing for adjustment of the relative angle between the holster holder and the belt.

8. (Original) The holster holder set forth in claim 7 wherein each of the belt receiving slots further comprises adjustment means for adjusting the height and the angle at which the belt passes through the slot.

9. (Withdrawn) The holster holder set forth in claim 1 further comprising a U-shaped slot for attachment of the plate to a portion of the wearer's clothing in a clip-on manner.

10. (Currently Amended) A holster holder for securing a holster to a wearer in a desired attitude, the holster holder comprising:

a plate;

means for attaching a holster to a side of the plate; and

at least two slots defined through the plate for receiving and securing a wearer's belt to the plate; and

repositionable adjustment means extending through each slot for adjusting a the relative height and angle of the plate with respect to the belt.

11. (Original) The holster holder set forth in claim 10 wherein the plate comprises at least three belt receiving slots defined therethrough and wherein two of the belt receiving

slots are formed in a vertical manner such that one is above the other, thereby providing alternative paths for the belt through the plate, thereby providing for adjustment of the relative angle between the holster holder and the belt.

12. (Currently Amended) The holster holder set forth in claim 10 wherein the means for attaching a holster to the plate comprises a first arcuate slot defined through the plate and comprising a first fastening means extending therethrough; a second arcuate slot defined through the plate, opposite to the first arcuate slot, the second arcuate slot comprising a mirror image of the first arcuate slot and comprising a second fastening means extending therethrough; a third slot defined through the plate below the first and second slots, the third slot having a recurvate ~~mustache~~ shape and comprising a third fastening means extending therethrough; wherein the three fastening means are capable of engaging three points of attachment defined on a holster; and wherein the relative angle of the holster to the plate is adjustable by coordinated adjustment of the three fastening means within each of the three slots.

13. (Currently Amended) The holster holder set forth in claim 11 wherein the means for attaching a holster to the plate comprises a first arcuate slot defined through the plate and comprising a first fastening means extending therethrough; a second arcuate slot defined through the plate, opposite to the first arcuate slot, the second arcuate slot comprising a mirror image of the first arcuate slot and comprising a second fastening means extending therethrough; a third slot defined through the plate below the first and second slots, the third slot having a recurvate ~~mustache~~ shape and comprising a third fastening means extending therethrough; wherein the three fastening means are capable of engaging three points of attachment defined on a holster; and wherein the relative angle of the holster to the plate is adjustable by coordinated adjustment of the three fastening means within each of the three slots.